Kast



Wall mounted up and downlighters

Wall mounted linear luminaires with upward and downward light component. Steel body finished in either white or black with opal polycarbonate diffusers. Can be mounted vertically as well as horizontally. Kast is ideal for corridors or stairwell applications.

Applications: corridors, stairwells, reception areas, meeting rooms, offices.

- Can be mounted horizontally or vertically
- Integral emergency and SmartScan emergency options
- SmartScan wireless technologyremoves the need for control cabling. Ideal for retrofit



IP40

IK10

Up to 130 LL/CW





Specification

Mounting Surface IP rating IP40

Impact rating IK10 Max presence detection height 8 m

Lighting

Optic Opal diffuser Lumen output 1,455 lm - 2,860 lm

Efficacy Up to 130 LL/CW

Emergency data

Emergency lumen output 385 lm Emergency type Maintained

Emergency duration 3 hours Battery specification Nickel Metal Hydride (NiMH)

Power

LED power 10 W - 20 W Circuit power 12 W - 22 W



LED characteristics

CRI 80+ Colour temperature 4000 K

Rated life (hours) 67 K - L80/B10


Compliance

UKCA Yes CE Yes

Energy efficiency class This product contains a light source

of energy efficiency class B

Dimensions

















Click or scan here

View Kast variants using our online filtering tool



Information is correct as of 30 Jan 2025, however must not be interpreted as a guarantee of individual product performance and/or characteristics. We reserve the right to alter specifications and designs without prior notice.