

Edge-lit emergency exit signs with SmartScan wireless communication

LED emergency exit signs with a choice of acrylic legend panels. Optional mounting kits for wall, cantilever or semi-recessed mounting. Three hour, maintained emergency operation and SmartScan wireless communication versions.

Applications: commercial environments, education, hospitals and retail.

- Low power consumption (1 W total)
- Extremely long LED lifetime, up to 100,000 hours
- 19.5 m maximum viewing distance in accordance with BS EN 1838
- Ceiling mounted with optional kits for wall, cantilever and semi-recessed mounting
- Choice of legends
- Status indicator shows operational condition
- Reliable Nickel Metal Hydride (NiMH) battery technology



IP40

0 LL/CW

Specification

Mounting	Surface	IP rating	IP40
----------	---------	-----------	------

Emergency data

Legend type	EURO arrow down EURO arrow left EURO arrow left / right double sided EURO arrow right ISO 7010 arrow down ISO 7010 arrow left ISO 7010 arrow left / right double sided ISO 7010 arrow right ISO 7010 arrow up	Maximum viewing distance	19.5 m
Emergency type	Maintained (wire link may be removed to enable non-maintained operation)	Emergency duration	3 hours
Battery specification	Nickel Metal Hydride (NiMH)		

Power


LED power	1 W	Circuit power	1 W
-----------	-----	---------------	-----

Compliance


UKCA Yes CE Yes

Dimensions


Ceiling Mounting




Cantilever Mounting



Wall Mounting



Semi Recessed



Click or scan here
View Lex variants using our
online filtering tool



Information is correct as of 30 Jan 2025, however must not be interpreted as a guarantee of individual product performance and/or characteristics. We reserve the right to alter specifications and designs without prior notice.