

## LED area floodlights

Stylish IP66 rated pole top amenity luminaire with aluminium cast body and spigot adaptor. UV stabilised polycarbonate cover rated IP66 and IK10. Integral high quality LED driver.

Applications: car parks, amenity areas and hospital estates.

- Integral high efficiency driver
- Extremely efficient and long system life up to 100,000 hours
- Fits 76mm columns as standard (60mm to special order)
- Photocell option
- Zero upward light
- SmartScan wireless technology removes the need for control cabling. Ideal for retro-fit



IP66

IK10

Up to 104.3 LL/CW

SMARTSCAN

## Lighting management

Lighting control system

Non-dimming  
SmartScan External

Emergency system

Non-emergency

## Specification

Mounting

Column

IP rating

IP66

Impact rating

IK10

Windage rating

0.06 m<sup>2</sup>

Max presence detection height

8 m

## Lighting

Optic

Clear cover

Lumen output

6,360 lm - 9,155 lm

Efficacy

Up to 104.3 LL/CW

## Power

LED power

52 W - 78 W

Circuit power

61 W - 89 W

## LED characteristics

CRI

70+

Colour temperature

4000 K


Rated life (hours)

100 K - L90/B10

## Compliance

UKCA Energy efficiency class	Yes This product contains a light source of energy efficiency class D	CE SmartScan wireless standards compliance	Yes Europe: EN 300 220-1 V2.4.1/ EN 301 489-3 V1.6.1. Australasia: ACMA 2014 Radio Communication Standard 2014. Thorlux Patented Wireless Technology - GB2575724
---------------------------------	--	---	---

## Dimensions



View the range



Information is correct as of 16 Oct 2024, however must not be interpreted as a guarantee of individual product performance and/or characteristics. We reserve the right to alter specifications and designs without prior notice.