

LED area floodlights

Stylish IP66 rated pole top amenity luminaire with aluminium cast body and spigot adaptor. UV stabilised polycarbonate cover rated IP66 and IK10. Integral high quality LED driver.

Applications: car parks, amenity areas and hospital estates.

- Integral high efficiency driver
- Extremely efficient and long system life up to 100,000 hours
- Fits 76mm columns as standard (60mm to special order)
- Photocell option
- Zero upward light
- SmartScan wireless technology removes the need for control cabling. Ideal for retro-fit



IP66
IK10
Up to 104.3 LL/CW
SMARTSCAN

Specification

Mounting	Column	IP rating	IP66
Impact rating	IK10	Windage rating	0.06 m ²
Max presence detection height	8 m		

Lighting

Optic	Clear cover	Lumen output	6,360 lm - 9,155 lm
Efficacy	Up to 104.3 LL/CW		

Power

LED power	52 W - 78 W	Circuit power	61 W - 89 W
-----------	-------------	---------------	-------------

LED characteristics


CRI	70+	Colour temperature	4000 K
Rated life (hours)	100 K - L90/B10		

Compliance

SmartScan wireless standards compliance

Europe: EN 300 220-1 V2.4.1/ EN 301 489-3 V1.6.1. Australasia: ACMA 2014 Radio Communication Standard 2014. Thorlux Patented Wireless Technology - GB2575724

Dimensions



View the range



Information is correct as of 21 Nov 2024, however must not be interpreted as a guarantee of individual product performance and/or characteristics. We reserve the right to alter specifications and designs without prior notice.