

Track mounted adjustable spotlights

Highly efficient track mounted spotlights with discrete integral control gear. Available in either narrow (19°), medium (33°) or wide (64°) beam distributions using Ra90 LEDs as standard, perfect for retail and display applications. Rotatable through 350° azimuth and 90° vertically for a full range of adjustment.

For use with the Track system.

- High performance reflector technology available in narrow (19°), medium (33°) and wide (64°) beam distributions
- 350° azimuth adjustment
- 90° vertical adjustment
- Suitable for installation into Global 3-circuit or DALI 3-circuit track
- Fitted with CRI 90 LEDs, suitable for retail applications
- Optional low glare honeycomb louvre



IP20

Up to 113.7 LL/CW

Lighting management

Lighting control system

Dimming (DALI)
Non-dimming

Emergency system

Non-emergency

Specification

Mounting

Track

IP rating

IP20

Lighting

Lumen output

2,170 lm - 2,830 lm

Efficacy

Up to 113.7 LL/CW

Power

LED power

19 W - 22 W

Circuit power

22 W - 26 W

LED characteristics

CRI

90+

Colour temperature

3000 K
4000 K


Rated life (hours)

85 K - L80/B10

Compliance

UKCA	Yes	CE	Yes
Energy efficiency class	This product contains a light source of energy efficiency class E		

Dimensions



View the range



Information is correct as of 16 Oct 2024, however must not be interpreted as a guarantee of individual product performance and/or characteristics. We reserve the right to alter specifications and designs without prior notice.