

## Retrofit kit for Prismalette luminaires

Energy saving, fast installation retrofit solution



### Lighting management

Lighting control system	Microwave Non-dimming SmartScan Radar	Emergency system	DALI / Self-Test Emergency Non-emergency SmartScan Emergency Standard Emergency
-------------------------	---	------------------	--

### Specification

Max presence detection height	Up to 4 m
-------------------------------	-----------

### Emergency data

Emergency type	Maintained	Emergency duration	3 hours
Battery specification	Nickel Metal Hydride (NiMH)		

### Power

LED power	11 W - 16 W	Circuit power	14 W - 20 W
-----------	-------------	---------------	-------------

### LED characteristics

CRI	80+	Colour temperature	4000 K
Rated life (hours)	100 K - L80/B10		

## Compliance

UKCA Energy efficiency class	Yes This product contains a light source of energy efficiency class B	CE SmartScan wireless standards compliance	Yes Europe: EN 300 220-1 V2.4.1/ EN 301 489-3 V1.6.1. Australasia: ACMA 2014 Radio Communication Standard 2014. Thorlux Patented Wireless Technology - GB2575724
---------------------------------	--	---	---



View the range



Information is correct as of 16 Oct 2024, however must not be interpreted as a guarantee of individual product performance and/or characteristics. We reserve the right to alter specifications and designs without prior notice.