

Corrosion resistant heavy duty bulkhead luminaires

Robust bulkhead luminaires for internal or external applications. Strong high-pressure die-cast aluminium body and frame with polycarbonate or thermally shock resistant borosilicate glass cover. Optional wire guard available.

Applications: walkways, loading bays, entrances, precincts and security areas. Ideal for industrial areas and power stations, cable tunnels, pump rooms and coal handling plants.

- Fixings outside gasket line to preserve IP rating
- Clip-on nylon coated steel wire guard available
- Tamper-resistant cover screws available
- Complies with M.O.D. JSP482 Chapter 8 Document for 'Category C' areas



IP66

Up to 115 LL/CW

LED PROTECT

Lighting management

Lighting control system

Non-dimming

Emergency system

Non-emergency

Specification

Mounting

Surface

IP rating

IP66

Lighting

Optic

Prismatic cover

Lumen output

2,455 lm - 4,255 lm

Efficacy

Up to 115 LL/CW

Power

LED power

20 W - 32 W

Circuit power

23 W - 37 W

LED characteristics

CRI

70+

Colour temperature

4000 K


Rated life (hours)

100 K - L90/B10

Compliance

UKCA	Yes	CE	Yes
Energy efficiency class	This product contains a light source of MOD compliance energy efficiency class C		JSP482 Chapter 8 Document for 'Category C' areas

Dimensions



View the range

Information is correct as of 16 Oct 2024, however must not be interpreted as a guarantee of individual product performance and/or characteristics. We reserve the right to alter specifications and designs without prior notice.