

## Architectural surface mounted LED exit signs

Emergency exit sign luminaires with acrylic legend panel. Suitable for ceiling, wall or cantilever mounting.

Applications: commercial and retail environments.

- Low power consumption (1 W total)
- Extremely long LED lifetime, up to 100,000 hours
- Very easy battery compartment access
- Ceiling mounted with optional kits for wall and cantilever mounting
- 26 m maximum viewing distance in accordance with BS EN 1838
- Choice of legends
- Status indicator shows operational condition
- Reliable Nickel Metal Hydride (NiMH) battery technology



## Specification

Mounting	Surface	IP rating	IP20
----------	---------	-----------	------

## Emergency data

Legend type	EURO arrow down EURO arrow left EURO arrow left / right double sided EURO arrow right ISO 7010 arrow down ISO 7010 arrow left ISO 7010 arrow left / right double sided ISO 7010 arrow right ISO 7010 arrow up	Maximum viewing distance	26 m
Emergency type	Maintained	Emergency duration	3 hours
Battery specification	Nickel Metal Hydride (NiMH)		

## Power


LED power	4 W
-----------	-----

## Compliance


UKCA Yes CE Yes

## Dimensions


Ceiling Mounting



Wall Mounting



Cantilever Mounting



**Click or scan here**

View Seven variants using our online filtering tool



Information is correct as of 15 Jan 2025, however must not be interpreted as a guarantee of individual product performance and/or characteristics. We reserve the right to alter specifications and designs without prior notice.