

Master control and web interface with SmartScan wireless communication

Transmits SmartScan and SmartScan emergency luminaire status reports to the SmartScan web server. Monitors and controls up to 50 wireless luminaires - ideal for smaller projects. Controls emergency lighting testing dates/times and external lighting switching times.

- Polycarbonate body finished white (RAL9016)
- Central monitoring for up to 50 SmartScan and SmartScan emergency luminaires - ideal for smaller projects
- Central time control for SmartScan External luminaires
- Communicates with the SmartScan website using MQTT mobile telecommunications
- Enables scheduled emergency test times / dates managed using the SmartScan website
- Status Indicators show operational condition
- Software security updates will be provided for a minimum of 10 years
- Ethernet connection for alternate connectivity to SmartScan website



Notes: SmartScan Gateway Lite is limited to a single poll every 24 hours and no live occupancy detection option.



Lighting management

Lighting control system	SmartScan External SmartScan Internal SmartScan Radar
-------------------------	---


Specification

IP rating	IP65
-----------	------

Compliance

UKCA	Yes	CE	Yes
SmartScan wireless standards compliance	Europe: EN 300 220-1 V2.4.1/ EN 301 489-3 V1.6.1. Australasia: ACMA 2014 Radio Communication Standard 2014. Thorlux Patented Wireless Technology - GB2575724		

Dimensions



View the
range



Information is correct as of 16 Oct 2024, however must not be interpreted as a guarantee of individual product performance and/or characteristics. We reserve the right to alter specifications and designs without prior notice.