


## Wireless scene control of SmartScan luminaires

Impact resistant manual scene control for SmartScan luminaires. 12 buttons providing On (Eco), Off, 5 programmable scenes and 5 fixed dimming levels.

- 12 buttons providing On (Eco), Off, 5 programmable scenes and 5 fixed dimming levels
- Mains (230 V) or battery powered versions available
- Communicates wirelessly with SmartScan luminaires
- Mains versions have additional wireless connectivity allowing control from the SmartScan App (iOS and Android)
- Requires a 35 mm deep single-gang back box (mains version only)
- Battery version is supplied complete with batteries and self-adhesive tape and can be mounted directly to the wall
- Multiple touch plates can be used to provide multi-point control
- Programmable using the SmartScan programmer



## Lighting management

Lighting control system

SmartScan Internal  
SmartScan Radar

## Compliance

UKCA

Yes


CE

Yes

SmartScan wireless standards compliance

Europe: EN 300 220-1 V2.4.1/ EN 301 489-3 V1.6.1. Australasia: ACMA 2014 Radio Communication Standard 2014. Thorlux Patented Wireless Technology - GB2575724

## Dimensions





View the  
range



Information is correct as of 16 Oct 2024, however must not be interpreted as a guarantee of individual product performance and/or characteristics. We reserve the right to alter specifications and designs without prior notice.