


Circular recessed downlighters

Recessed luminaires with injection moulded reflector finished white. Open IP20 and frosted IP65 versions available in 14 W and 20 W.

Applications: reception areas, retail, public areas and toilets.

- Sprung suspension arms for rapid installation
- Supplied with remote gear unit fitted with 2 m lead
- Luminaires can be supplied pre-wired with a purpose made 1 m connection lead for plugging directly into the Smart Hub
- Fitted with CRI 90 LEDs with enhanced R9 value. Suitable for retail applications

Notes: CRI 80 version available to special order (minimum order quantity applies)



Up to IP65 (IP20 above ceiling)

Up to 91.7 LL/CW

Lighting management

Lighting control system

Dimming (DALI)
Non-dimming

Emergency system

Non-emergency

Specification

Mounting

Recessed

IP rating

Up to IP65 (IP20 above ceiling)

Lighting

Lumen output

1,270 lm - 2,110 lm

Efficacy

Up to 91.7 LL/CW

Power

LED power

14 W - 20 W

Circuit power

17 W - 23 W

LED characteristics

CRI

90+

Colour temperature

3000 K
4000 K


Rated life (hours)

50 K - L70/B10

Compliance

UKCA	Yes	CE	Yes
Energy efficiency class	This product contains a light source of energy efficiency class E		

Dimensions





View the range



Information is correct as of 16 Oct 2024, however must not be interpreted as a guarantee of individual product performance and/or characteristics. We reserve the right to alter specifications and designs without prior notice.